



MOBILE RAMP PYR



Model	Capacity (kg)	Total Width (mm)	Service Width (mm)	Lip (mm)	Working Range (mm)
PYR-8	8000	2350	1980	750	1000/1600
PYR-10	10000	2350	1980	750	1000/1600
PYR-12	12000	2350	1980	750	1000/1600
PYR-15	15000	2350	1980	750	1000/1600

* Please contact our sales teams for different dimensions and capacities

DESCRIPTION

Mobile loading ramps can be used for loading or unloading from zero to a height until 1000-1600 mm via forklifts and pallet trucks. Because the mobile loading ramps are portable, their position can easily be changed according to any situation.

OPTIONAL PROPERTIES

- Front Bumpers
- Forklift support plates for each sides
- 1200 mm high side protection barriers
- Electro-hydraulic system for lifting front and rear flaps

TECHNICAL PROPERTIES

- CE Certificate
- Steel construction designed for load distribution
- Front and rear flaps with high quality construction hinges
- Front flaps hydraulically foldable in two parts
- Front flaps made of 12/13 mm teardrop pattern plates
- Open length 10500 mm, closed length 8020 mm
- 350 mm high side protection barriers
- Movable soles for matching the ground
- High maneuverable heavy load castors
- Landing gear legs with two speed levels for height adjustment
- Manually operated hydraulic system for lifting front and rear flaps
- Platform floor made of galvanized forge-welded gratings for anti-slip



PagátGold